

## CONSTANT PRESSURE ADVERTISING SCREEN VENTO®

### MOUNTING SET




x 1

electric pump




x 4

straight pin with eyelet and extraction ropes




x 2

straight pin with eyelet




x 1

hammer



x 1


transport bag




x 1

repair set


### ASSEMBLY INSTRUCTION




- 1** Unfold the screen on a flat surface and detach the bottom lock.




- 2** Pin the cables to the lashing eyes in the screen.




- 3** Find the inflate/deflate valve on the side of the screen and unscrew the plug.




- 4** Block the valve by turning the diaphragm needle by turning the needle approx. 90° to the right, this prevents air escaping. The air release valve is unlocked by turning the needle approx. 90° to the left.




- 5** Connect the pump to the screen and wait until the screen fills with air.



- 6** Hold the zipper open for a moment to replenish the air inside and tighten the cover. Then fasten the zipper.



- 7A** Stand the screen up using the lashing ropes, they must be taut and stretched to their full length. Fix the pins to the lines and drive into the ground with a hammer. Stabilise the screen by fixing the pins to the ground in the base.



- 7B** For substrates that do not allow the use of pins/anchors, dedicated weights or weight bags should be used for the lashing lines.

## CONSTANT PRESSURE ADVERTISING SCREEN VENTO®


### MOUNTING SET




x 1  
electric pump




x 4  
straight pin with eyelet  
and extraction ropes




x 2  
straight pin  
with eyelet



x 1  
hammer




x 1  
transport bag



x 1  
repair set

### DISASSEMBLY INSTRUCTION


1 Remove all anchors/pins from the lashing lines.



3 Find the inflate/deflate valve and unscrew the the plug.

5 Assemble and pack the mounting kit in the accessory bag.

2 Place the product on a flat and dry surface.



4 Unlock the valve by turning the diaphragm needle approximately 90° to the left and start pumping air out of the product.

6 Roll the product towards the inflate/deflate valves into a built-up bag or pack it into a dedicated carry bag and zip it up.

### INSTRUCTION OF USE

1. Please read the product assembly/disassembly instructions before assembly.
2. When transporting, setting up and assembling the product, take special care to avoid damage to the product or injury during assembly.
3. Before disassembling the product, ensure that there are no sharp objects, tools, etc. with sharp edges in the area where the product will be assembled.
4. If using an electric pump, check the condition of the wires before connecting to avoid electric shock.
5. Do not cover the safety valves that regulate the air pressure in the product.
6. In case of very strong winds, systematically check the seating of the pins/anchors, when it blows more than 38km/h the product should be assembled immediately.
7. During rain or snowfall, excess water/snow should be systematically removed from the product.
8. Any soiling must be removed immediately with a damp cloth and warm water without the use of detergents. The use of high-pressure cleaners is prohibited.
9. The product should be cleaned and dry before disassembly. If, due to weather or other circumstances, the product is assembled wet and dirty, it should be disassembled again as soon as possible, dried and cleaned.
10. The product should be stored in a dry and clean place.



risk of ignition following contact with a fire or ignition source



risk of entanglement or tripping over lashing ropes



risk of overturning due to incorrect installation or strong winds



inappropriate use e.g. climbing



risk of damage to the power cable, e.g. on an electric pump